

[print](#) | [close](#)

## Creating Duplicate Object and Library Lists

[System iNetwork](#)

[Carsten Flensburg](#)

Carsten Flensburg

Fri, 06/01/2001 (All day)

Before V4R5, it was impossible to specify the special value \*LIBL for the CrtDupObj (Create Duplicate Object) command's FromLib parameter. In a CL program, however, you could circumvent this restriction by letting the RtvObjD (Retrieve Object Description) command retrieve a specific object's library name using a library list search; you could then supply the retrieved value to the CrtDupObj command's FromLib parameter.

As of V4R5, there's a much easier way to do this. You can enter \*LIBL in the FromLib parameter if you specify a single object name and a specific object type. The following command copies the file DTA001F to library QTEMP using a library list search to locate DTA001F.

```
CrtDupObj Obj( DTA001F )  
          FromLib( *LIBL )  
          ObjType( *FILE )  
          ToLib( QTEMP )  
          NewObj( *OBJ )  
          Data( *NO )
```

V4R5 also lets you specify FromLib (\*LIBL) from the command line.

*Carsten Flensburg, Programmer/Analyst*

*Novasol Data AS*

*Copenhagen, Denmark*

**Source URL:** <http://iprodeveloper.com/rpg-programming/creating-duplicate-object-and-library-lists>